

Flonfit

150°C Flexible Flame-Resistant PVDF Heat Shrink Tubing
150°C 柔软型阻燃PVDF热缩管

耐高温、柔韧、耐化学腐蚀防护
High-Temp, Flexible, Chemical-Resistant Protection

本管材采用辐照交联氟聚合物制成，具备卓越的耐化学性、耐溶剂性及耐磨损性能，能够在高温环境下稳定使用。其不仅为电线及电子元件提供可靠的绝缘、应力缓解与保护，同时便于清晰标识与便捷检测。

Manufactured from irradiation cross-linked fluoropolymer, this tubing offers outstanding chemical, solvent, and abrasion resistance at elevated temperatures. It ensures reliable insulation, strain relief, and protection for wires and electronic components, while also supporting clear identification and inspection.



产品特性与优势

Features and benefits

性能 Property	指标要求 Requirement	测试方法 Test Method	典型值 Typical Data
操作温度范围 Operating Temperature	/	/	-55°C to +150°C
最低收缩温度 Min. Shrink Temperature	/	/	+125°C
完全收缩温度 Full recovery temperature	/	/	+150 °C
纵向收缩率 Longitudinal shrinkage	≤10%	ASTM D 2671	≤5%
抗张强度 Tensile strength	≥17.3MPa	ASTM D 638	≥24.3MPa
断裂伸长率 Elongation at break	≥150%	ASTM D 638	≥300%
老化后断裂伸长率 Elongation at break after aging	≥100%	ASTM D 638	≥200%
热冲击 Heat Shock	无裂痕 No Cracking	ASTM D 2671 (275°C, 4hrs)	无裂痕 No Cracking
低温柔软性 Low-temperature flexibility	无裂痕 No Cracking	ASTM D 2671 (-55°C, 4hrs)	无裂痕 No Cracking
绝缘耐压和击穿 Dielectric voltage withstand	无击穿 No Breakdown	ASTM D 2671 (2500V, 60s)	无击穿 No Breakdown
体积电阻率 Volume resistivity	≥10 ¹¹ Ω·cm	ASTM D 876	≥10 ¹² Ω·cm
腐蚀性 Corrosion	无腐蚀 No Corrosion	ASTM D 2671	无腐蚀 No Corrosion
阻燃性 Flammability	VW-1	UL224	VW-1

- 收缩比: 2:1
 - 柔软, 高阻燃
 - 具备优良的韧性与耐磨性
 - 透光性极佳, 性能稳定
 - 满足环保要求
- Shrink Ratio: 2:1
 - Highly flame-resistant and flexible
 - Good toughness and abrasion resistance
 - Excellent clarity and stability
 - Meets environmental requirements.

颜色

COLOR



https://www.hzdingyuan.cn/




表 A. 产品规格
Table A. Product Dimensions

编号 Part No.	规格 Size (Φ mm)	收缩前 As supplied (mm)	收缩后 After recovered (mm)	标准包装 Standard packing (m/pc, m/roll)
		最小内径 I.D min(D)	最大内径 I.D max (d)	
Flonfit-150FV-1.2	1.2 (3/64")	1.2	0.6	1.22/200
Flonfit-150FV-1.6	1.6 (1/16")	1.6	0.8	1.22/200
Flonfit-150FV-2.4	2.4 (3/32")	2.4	1.2	1.22/200
Flonfit-150FV-3.2	3.2 (1/8")	3.2	1.6	1.22/200
Flonfit-150FV-4.8	4.8 (3/16")	4.8	2.4	1.22/100
Flonfit-150FV-6.4	6.4 (1/4")	6.4	3.2	1.22/100
Flonfit-150FV-9.5	9.5 (3/8")	9.5	4.8	1.22/100
Flonfit-150FV-12.7	12.7 (1/2")	12.7	6.4	1.22/50
Flonfit-150FV-19.1	19.1 (3/4")	19.1	9.5	1.22/50
Flonfit-150FV-25.4	25.4 (1")	25.4	12.7	1.22/50
Flonfit-150FV-38.1	38.1 (3/2")	38.1	19.1	1.22/50

接受特殊尺寸及颜色定制需求, 技术参数如有变更, 恕不另行通知。最低订购量 (MOQ) 可能与包装数量有所不同。

Custom sizes and colors are available upon request. Technical specifications are subject to change without prior notice. Minimum order quantities (MOQ) may differ from standard packaging quantities.